

## HSL Self Locks

### Longer Runs Without Mid-Support



The Artex HSL self lock system offers added stability for rougher applications. This heavy-duty self lock system features a 70 mm (2.75") square top and bottom rail and enables you to install long runs up to 6 m (20') without the need for intermediate support. The HSL self lock is also designed for use with feed stalls.

#### STANDARD FEATURES FOUND ON ALL ARTEX SELF LOCKS

- Rub-Free Flippers
- Noise Reducing Hardware
- Quick Release Mechanisms
- Individual Animal Lock-Ups
- Auto-Open Top
- Bottom Blocker
- Visual Lock-Unlock Settings
- Pre-Galvanized or Hot Dipped Galvanized Options

#### SPECIAL FEATURES FOUND ON HSL SELF LOCKS

- 70 mm (2.75") Heavy-Duty Top Rail
- 70 mm (2.75") Heavy-Duty Bottom Rail
- Easy Connection for Feed Stalls
- Fewer Intermediate Posts Required

#### STANDARD AVAILABLE SIZES

- 2.40 m (8') - 3 openings
- 2.50 m (8' 2") - 3 openings
- 3.05 m (10') - 5 openings
- 3.66 m (12') - 6 openings
- 4.00 m (13' 5") - 6 openings
- 4.25 m (14') - 7 openings
- 4.56 m (15') - 7 openings
- 4.88 m (16') - 8 openings
- 4.88 m (16') - 10 openings



**OPTIMIZE BUNK SPACE & INCREASE COW COMFORT**

Add feed stalls to your HSL self locks and prevent scrapers from disturbing your cows while eating. Available in pre-galvanized and fully hot dipped galvanized options.

